



LOUIS ADHESIVE TAPES CO., LTD.

1070 Soi Suanplu, South Sathorn Rd., Bangkok 10120 Thailand

Tel : (662) 2872100 (12 Lines), 2864223-6, 2874326-8

Fax : (662) 2871101 (direct), 2874736

E-mail : export@louistapes.com URL : www.louistapes.com



Antistatic Tape - No. 102

The tape suppresses static electricity both during unwinding from a roll and during removal from a surface. Suitable for sensitive electronic parts, medical equipment, precision components or other applications in static-sensitive areas.

Features

- Biodegradable cellulose film coated with natural rubber-based adhesive.
- Surface resistivity (ASTM-D257):
 - Film side - 6×10^8 Ohms.
 - Adhesive side - 5×10^9 Ohms.
- Suppresses static during unwinding from roll and during removal from a surface.
- Available in clear and printed ESD susceptibility symbol.
- Alternative to: Tesa #53205; Shurtape #CT109; Clipper #4206; Scapa #1109 and Intertape #MC-1

Applications

- Sealing ESD bags and other ESD packaging/container.
- Secure (bundle) IC DIP tube.
- Ideal for general application in static-sensitive areas.
- Suitable for sensitive electronic parts, clean rooms, medical equipment, or precision components.

Code No.	Adhesive Type	Thickness	Length	Core Size
102	Rubber Solvent Based	$46\mu \pm 10\%$	66 M	3 inches